Philips
LCD widescreen monitor

20.1" wide
WSXGA+

200CW8FB

Elegant Widescreen performance

View all your favorite entertainment on a single wide screen display with the Philips 200CW8 featuring a bigger, high resolution screen, fast response time, dual input options and great viewing comfort in an easy-to-use package.

Outstanding front of screen performance

- Big, wide screen: IM, write mail, watch videos on one screen
- SmartImage: For an optimized display experience
- SmartContrast: Dynamic,optimized contrast for visual clarity
- Optimize response time for different viewing requirements
- DVI-D input and HDCP support
- PerfecTune ensures top quality LCD display delivered to you
- Empowered for Windows Vista

Great convenience

- SmartAccessory to personalize and organize your workspace
- Hassle-free display performance tuning with SmartControl II
- USB port for convenient peripheral connections

Green design

- For your safety: Aerospace composite fire retardant case
- TCO'06 compliance for a better multimedia experience

PHILIPS
sense and simplicity

LCD widescreen monitor
20.1" wide WSXGA+

200CW8FB/05

Specifications

Picture/Display
- LCD panel type: 1680 x 1050 pixels, Anti-glare polarizer, RGB vertical stripe
- Panel Size: 20.1"/ 51 cm
- Effective viewing area: 433.4 x 270.9 mm
- Pixel pitch: 0.258 x 0.258 mm
- Brightness: 300 cd/m²
- Contrast ratio (typical): 1000:1
- SmartContrast ratio (dynamic): 3200:1
- Display colors: 16.7 M
- Viewing angle: 160° (H) / 160° (V), @ C/R > 10
- Response time (typical): 5 ms
- SmartResponse: 2 ms (Gray to Gray)
- Maximum Resolution: 1680 x 1050 @ 75Hz (digital input)
- Recommended Resolution: 1680 x 1050 @ 60Hz (digital input)
- Video Dot Rate: 205 MHz
- Horizontal Scanning Frequency: 30 - 83 Hz
- Vertical Scanning Frequency: 56 - 76 Hz
- Picture enhancement: SmartImage
- sRGB

Connectivity
- Signal Input: Analog (VGA), DVI-D
- USB: 1 x USB 2.0
- Video Sync Input Signal: Composite Sync, Separate Sync, Sync on Green

Convenience
- Convenience Enhancements: On-screen Display, SmartControl II
- Monitor Controls: SmartImage, Auto (Back), Input (Down), Brightness (Up), Menu (OK), Power On/Off
- OSD Languages: English, French, German, Italian, Portuguese, Russian, Simplified Chinese, Spanish
- Other convenience: Kensington lock compatible
- Plug & Play Compatibility: DDC/CI, sRGB, Windows 98/ME/2000/XP/Vista
- Regulatory Approvals: CE Mark, EMC, Energy Star, FCC-B, UL, CSA, TCO '06
- Tilt: -5° to 20°

Accessories
- Included Accessories: AC Power Cord, VGA cable
- User Manual

Dimensions
- Box dimensions (W x H x D): 535 x 451 x 159 mm
- Box dimensions in inch (W x H x D): 21.1 x 17.8 x 6.3 inch
- Set dimensions (W x H x D): 480 x 321 x 65 mm
- Set dimensions in inch (W x H x D): 18.9 x 12.6 x 2.6 inch
- Set dimensions with stand (W x H x D): 480 x 393 x 193 mm
- Set dimensions with stand in inch (W x H x D): 18.9 x 15.5 x 7.6 inch
- MTBF: 50,000 (excl. CCFL 40,000) hrs
- Relative humidity: 20% - 80%
- Temperature range (operation): 0°C to 40°C
- Temperature range (storage): -20°C to 60°C
- Product weight (+stand): 4.87 kg
- Product weight (+stand) (lb): 10.7 lb
- Weight incl. Packaging: 6.76 kg
- Weight incl. Packaging (lb): 14.9

Power
- Complies with: Energy Star
- Consumption: < 45 W (Typical)
- Consumption (economy mode): 31 W
- Off Mode: < 1 W
- Power LED indicator: Operation - green, Stand by/sleep - Amber
- Power supply: Built-in, 100-240VAC, 50/60Hz

Product highlights

Widescreen design
A wide screen has a wider aspect ratio for displaying more entertainment or information to have more fun and get more done.

SmartImage
SmartImage is an exclusive, leading edge Philips technology that analyzes the content displayed on your screen. Based on a scenario you select, SmartImage dynamically enhances the contrast, color saturation and sharpness of images and videos for ultimate display performance - all in real time with the press on a single button.

SmartContrast
SmartContrast is Philips technology that analyzes the contents you are displaying, automatically adjusting colors and controlling backlight intensity to dynamically enhance contrast for the best digital images and optimum contrast for more entertainment fun when viewing videos or playing games where dark hues are displayed; when you select the Economy mode, contrast is adjusted and backlighting fine-tuned for just-right display of everyday office applications and lower power consumption.

SmartResponse
SmartResponse is exclusive Philips technology that adjusts response time to application requirements, delivering faster response times for gaming and videos or better color saturation for viewing photos and static images.

PerfecTune
PerfectTune is industry-leading, proprietary Philips testing and algorithm technology for monitor adjustment and fine tuning, an extensive process that ensures ultimate display performance in compliance with a standard four-times more stringent than Microsoft's Vista requirements from each and every monitor that leaves the factory - not just a few review samples. Only Philips goes to these lengths to deliver this exacting level of color accuracy and display quality in every new monitor.

SmartAccessory
SmartAccessory is an innovative and friendly solution for easily and flexibly attaching peripherals like a webcam or stationery onto a monitor frame to keep your space tidy and organized. It is equipped with multifunction clips with a universal interface that attaches to the monitor frame and moves up and down or left and right to accommodate a variety of included or optional holders for stationery, small peripherals like webcams, conveniently locating work or personal items in your line of sight and at your fingertips.

SmartControl II
SmartControl II is monitor-based software with an easy-to-use on-screen graphic interface that guides you through fine-tuning resolution, color calibration and other display settings including brightness, contrast, clock & phase, position, RGB, white point and - on models with onboard speakers - volume adjustments.

USB 2.0 port
The universal serial bus or USB is a standard protocol for linking PCs and peripherals. Because it delivers high speed at a low cost, USB has become the most popular method for connecting peripheral devices to a computer. A port located on a monitor directly in the user's line of sight provides easy, high-speed connectivity for USB devices at a convenient location. (USB 2.0 support is dependent on your PC's USB configuration; when connected to a PC that supports USB 2.0, your monitor is USB 2.0 compatible)

Issue date 2008-11-15

Version: 3.0.1

12 NC: 8670 000 37884
EAN: 87 12581 40283 9

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com